Docket No.: SONY 3.0-042

This listing of claims will replace all prior versions and listings of claims in the application:

IN THE CLAIMS

(currently amended) An apparatus, comprising:

<u>a) at least</u> one <u>or more mobile items</u> operable to be carried by a user, <u>each</u> and including a radio frequency tag operable to produce an answer electromagnetic wave in response to a query electromagnetic wave; and

b) a toy including a query circuit and an interaction circuit, the query circuit being operable to emit the query electromagnetic wave and receive one or more of the answer electromagnetic waves from the one or more mobile items, and the interaction circuit being operable to i) associate a userdefined output with one or more of the answer electromagnetic waves; ii) select the user-defined output based on receiving the associated one or more answer electromagnetic waves; iii) simultaneously_select an—a second output from among a plurality of outputs based on receiving a particular one or more of the and iv) electromagnetic waves; output, answer manner, the selected user-defined output user-perceptible combined with the simultaneously selected second output. by the user based on the answer electromagnetic wave.

- 2. (currently amended) The apparatus of claim 1, wherein the interaction circuit includes an output circuit coupled to at least one output transducer operable to produce the output perceptible by the user-defined output and the second output.
- 3. (original) The apparatus of claim 2, wherein the at least one output transducer includes at least one of an audio transducer, a visual transducer, a tactile transducer, and a mechanical transducer.



Docket No.: SONY 3.0-042

- 4. (currently amended) The apparatus of claim 3, wherein the user-defined output includes a user-defined phrase and the second output includes a second phrase, wherein the interaction circuit is operable to audibly output the user-defined phrase and the second phrase. select at least one phrase from among a plurality of phrases based on the answer electromagnetic wave, the output circuit is operable to produce an output signal corresponding to the selected phrase, and the output transducer includes the audio transducer, which is operable to produce an audible phrase corresponding to the selected phrase.
- 5. (currently amended) The apparatus of claim 4, comprising at least two of the mobile items each operable to produce a respective answer electromagnetic wave in response to a query electromagnetic wave, wherein the interaction circuit is operable to select at least one of the user-defined phrase and the second phrase the at least one phrase based on which of the one or more of the answer electromagnetic waves are—is received.
 - 6. (canceled)
- 7. (currently amended) The apparatus of claim—6_4, wherein the interaction circuit is operable to receive the user_defined phrase from the user and to store the user-defined phrase, wherein the interaction circuit is operable to select the stored user-defined phrase for output. and associate the user_defined phrase with one or more of the answer electromagnetic waves specified by the user.
- 8. (currently amended) The apparatus of claim 7, wherein the interaction circuit is operable to associate the user-defined phrase with the one or more electromagnetic waves permit the user to specify the one or more of the answer electromagnetic waves—by the user selecting one or more of the mobile items.
 - 9. (currently amended) An apparatus, comprising:



Docket No.: SONY 3.0-042

a plurality of radio frequency tags operable to produce respective answer electromagnetic waves in response to a query electromagnetic wave; and

a toy including a query circuit and an interaction circuit, the query circuit being operable to emit the query electromagnetic wave and receive one or more of the answer waves, and the interaction circuit electromagnetic operable to i) associate a user-defined output with one or more of the answer electromagnetic waves; ii) select the user-defined output based on receiving the associated one or more answer electromagnetic waves; iii) simultaneously select a second output from among a plurality of outputs based on receiving a particular one or more of the answer electromagnetic waves; and iv) to output, in order, in user-perceptible manner, the selected user-defined output and the simultaneously selected second output. select an output perceptible by a user based on which of the one or more answer electromagnetic waves are received.

- 10. (currently amended) The apparatus of claim 9, wherein one or more of the radio frequency tags are disposed at respective physical locations, and the interaction circuit is operable to select at least one of the user-defined output and the second output from among a plurality of outputs based on which one or more answer electromagnetic waves are received.
- 11. (original) The apparatus of claim 10, wherein at least one of the radio frequency tags is operable to produce an answer electromagnetic wave that is distinguishable from others of the answer electromagnetic waves, and the interaction circuit is operable to select at least one output from among the plurality of outputs by distinguishing which one or more of the answer electromagnetic waves are received.
- 12. (original) The apparatus of claim 11, wherein at least one of the radio frequency tags is operable to produce an answer

electromagnetic wave including at least one of: (i) frequency of content that is different from others the electromagnetic waves, and the interaction circuit is operable to distinguish which one or more of the answer electromagnetic waves are received based on the frequency content thereof; a code that is different from others of the answer electromagnetic waves, and the interaction circuit is operable to distinguish which one or more of the answer electromagnetic waves are received based on the codes thereof.

- (currently amended) The apparatus of claim 12, wherein the interaction circuit is operable to store indications which one or more of the answer electromagnetic waves are received.
- (original) The apparatus of claim 13, wherein the 14. indications are at least one of assigned, tagged, and created index numbers.
- (currently amended) The apparatus of claim 14, wherein the interaction circuit is operable to select at least one of the user-defined output and the second output based on which of the index numbers were stored.
- (original) The apparatus of claim 10, wherein the plurality of outputs include characteristics that correspond to respective characteristics of the physical locations.
- The apparatus of claim 16, wherein the (original) respective characteristics of the physical locations include a type of room in which a given one of the radio frequency tags is disposed.
- (original) The apparatus of claim 17, wherein the type 18. of room is taken from the group consisting of: a kitchen, a dining room, a family room, a bedroom, living room, a bathroom, a basement, a garage, a foyer, an attic, and a



Docket No.: SONY 3.0-042

- 19. (currently amended) The apparatus of claim 17, wherein the interaction circuit includes an output circuit coupled to at least one output transducer operable to produce the output the user-defined output and the second output. perceptible by the user.
- 20. (original) The apparatus of claim 19, wherein the at least one output transducer includes at least one of an audio transducer, a visual transducer, a tactile transducer, and a mechanical transducer.
- 21. (currently amended) The apparatus of claim 20, wherein the user-defined output includes a user-defined phrase and the second output includes a second phrase, wherein said interaction circuit is operable to select at least one—the user-defined phrase and the second phrase from among a plurality of phrases based on which of the first one or more and the second one or more answer electromagnetic waves is received, and said the—output circuit is operable to produce an—audibly output the user-defined phrase and the second phrase. signal corresponding to the selected phrase, and the output transducer includes the audio transducer, which is operable to produce an audible phrase corresponding to the selected phrase.
- 22. (currently amended) The apparatus of claim 21, wherein at least one of the selected user-defined phrase and the selected second phrase includes the characteristics that correspond to the respective characteristics of the physical locations at which one or more of the radio frequency tags are disposed and from which one or more answer electromagnetic waves are received.
 - 23. (canceled)
- 24. (currently amended) The apparatus of claim 23, wherein the interaction circuit is operable to receive the user—defined phrase from the user and to store the user-defined phrase, and to select the stored user-defined phrase. associate the user



Docket No.: SONY 3.0-042

defined phrase with one or more of the answer electromagnetic waves specified by the user.

- 25. (currently amended) The apparatus of claim 24, wherein the interaction circuit is operable to associate the user-defined phrase with permit the user to specify—the one or more of the answer electromagnetic waves by the user selecting one or more of the radio frequency tags.
 - 26. (currently amended) A method, comprising:

providing at least one mobile item operable to be carried by a user and emit an answer electromagnetic wave in response to receiving a query electromagnetic wave;

providing a toy operable to emit the query electromagnetic wave and receive the answer electromagnetic wave;

associating a user-defined output with one or more of the answer electromagnetic waves;

selecting the user-defined output based on receiving the associated one or more answer electromagnetic waves;

simultaneously selecting a second output from among a plurality of outputs based on receiving a particular one or more answer electromagnetic waves;

outputting, in user perceptible manner from the toy,
the selected user-defined output combined with the
simultaneously selected second output.and

--- selecting an output to issue from the toy that is perceptible by the user based on the answer electromagnetic wave.

27. (currently amended) The method of claim 26, wherein the toy includes at least one output transducer operable to produce the output perceptible by the user-defined output and the second output, and the at least one output transducer includes at least one of an audio transducer, a visual transducer, a tactile transducer, and a mechanical transducer.



- 28. (canceled)
- 29. (currently amended) The method of claim—28_27, further comprising:

providing at least two mobile items each operable to produce a respective answer electromagnetic wave in response to a query electromagnetic wave; and

selecting the at least one of the user-defined output and the second output phrase based on which one or more of the answer electromagnetic waves are received.

30. (currently amended) The method of claim 28, wherein the user-defined output includes a user-defined phrase and the second output includes a second phrase. further comprising associating a user defined phrase with one or more of the answer electromagnetic waves; and

- 31. (currently amended) The method of claim 30, further comprising receiving the user—defined phrase from the user and storing the user-defined phrase, wherein said selecting selects the stored user-defined phrase. and associating the user defined phrase with one or more of the answer electromagnetic waves specified by the user.
- 32. (currently amended) The method of claim 31, wherein said associating includes further comprising permitting the user to—specifying the one or more of the answer electromagnetic waves by selecting one or more of the mobile items by the user.
- 33. (currently amended) The method of claim 26, further comprising:

providing a plurality of radio frequency tags operable to produce respective answer electromagnetic waves in response to the query electromagnetic wave, wherein the user-defined output and the second output are selected; and



Docket No.: SONY 3.0-042


which of the one or more answer electromagnetic waves are received from the at least one mobile item and the plurality of radio frequency tags.

- 34. (currently amended) The method of claim 33, further comprising disposing one or more of the radio frequency tags at respective physical locations, wherein the second; and selecting at least one output is selected from among a plurality of outputs corresponding to respective characteristics of the physical locations, based on which of the one or more answer electromagnetic waves are—is received.
- (currently amended) The method of claim 34, wherein at least one of the radio frequency tags is operable to produce an answer electromagnetic wave that is distinguishable from others further the method electromagnetic waves, of the answer output from selecting at least one among comprising plurality of outputs by distinguishing which of the one or more of the answer electromagnetic waves are is received.
- 36. (currently amended) The method of claim 35, wherein at least one of the radio frequency tags is operable to produce an answer electromagnetic wave including at least one of: (i) frequency content that is different from others of the answer electromagnetic waves; and (ii) a code that is different from others of the answer electromagnetic waves, the method further comprising distinguishing which of the one or more of the answer electromagnetic waves are is received based on at least one of the frequency content and the codes thereof.
- 37. (currently amended) The method of claim 36, further comprising storing indications of which of the one or more of the answer electromagnetic waves are is received.
- 38. (original) The method of claim 37, wherein the indications are at least one of assigned, tagged, and created index numbers.



- 39. (currently amended) The method of claim 38, further comprising selecting at least one of the user-defined output and the second output based on which of the index numbers are were stored as indications of receiving the one or more answer electromagnetic waves.
 - 40. (canceled)
- 41. (currently amended) The method of claim—40_34, wherein the respective characteristics of the physical locations include a type of room in which a given one of the radio frequency tags is disposed.
- 42. (original) The method of claim 41, wherein the type of room is taken from the group consisting of: a kitchen, a living room, a dining room, a family room, a bedroom, a bathroom, a basement, a garage, a foyer, an attic, and a hallway.
 - 43. (canceled)
 - 44. (canceled)
- 45. (currently amended) The method of claim—44_34, wherein the second output includes a selected phrase includes the characteristics that—corresponding to the respective characteristics of the physical locations at which one or more of the radio frequency tags are disposed and from which one or more of the answer electromagnetic waves are—is_received.
 - 46. (canceled)
 - 47. (canceled)
- 48. (new) The apparatus of claim 1 wherein the interaction circuit is further operable to output the user-defined output and the second output in order.
- 49. (new) The apparatus of claim 1 wherein the interaction circuit is operable to select the second output based on receiving the answer electromagnetic wave that is associated with the user-defined output.
- 50. (new) The apparatus of claim 1 wherein the particular answer electromagnetic wave, based on receipt of which the





second output is selected is different from the answer electromagnetic wave associated with the user-defined output.



51. (new) The method of claim 26 wherein the user-defined output includes a user-defined phrase and the second output includes a second phrase and the user-defined phrase and the second phrase are outputted in order.